


		<p>TC-T OSRAM: DULUX T PHILIPS: PL-T</p> <p>HIT-DE OSRAM: HQI-TS, HCI-TS PHILIPS: MHN-TD, CDM-TD</p> <p>HIT-CE OSRAM: HCI-T PHILIPS: CDM-T</p> <p>HST-DE OSRAM: NAV-TS PHILIPS: -</p>	<p>2600 ATLANTIQUE DRIVE OVER</p> <p>IP68 CE F IK 10</p>
<ul style="list-style-type: none"> • Body from aluminium alloy. • Locking ring (flange) from aluminium alloy or AISI 316 stainless steel. • 12mm clear flat tempered glass cover. 		<p>PRICE LIST</p> <p>Integrated Control Gear</p>	
CODE	DESCRIPTION (for aluminium ring luminaires)	T	COLOUR
842775	80 20 174 2x56,8° 1x26W TC-T / GX24d-3	73°C	Black
842785	80 20 055 2x5° 1x35W HIT-CE / G12	80°C	Black
842795	80 20 056 2x25° 1x35W HIT-CE / G12	78°C	Black
842805	80 20 036 2x5° 1x70W HIT-CE / G12	130°C	Black
842815	80 20 044 2x25° 1x70W HIT-CE / G12	111°C	Black
842825	80 20 163 asym.10° 1x70W HIT-DE or HST-DE / RX7s	120°C	Black
804213	Outercasing 89 36 000		

T Glass surface temperature.

Resistance to static load: max. 4.500kg.



For the proper installation of the fitting an effective drainage as well as a 20-30 cm deep layer of gravel must be intended for dewatering.

Fittings come with H07RNF cables, 3m length.

<p>AISI 316 stainless steel ring.</p>		<p>2600 ATLANTIQUE - ACCESSORIES RING</p>	
<p>PRICE LIST</p>			
CODE	DESCRIPTION	COLOUR	
804214	RING 89 20 000		

<p>Anti-vandalism protection grid "GPA".</p>		<p>2600 ATLANTIQUE - ACCESSORIES ANTI-VANDALISM GRID</p>	
<p>PRICE LIST</p>			
CODE	DESCRIPTION	COLOUR	
804215	ANTI-VANDALISM GRID 89 22 000		