


		PAR 30 HIT-TC-CE / G8.5 OSRAM: HCI-TC PHILIPS: CDM-TC	<b>2100 MEDIO Inox</b> <b>DRIVE OVER</b>			
		<ul style="list-style-type: none"> <li>• Body from aluminium alloy.</li> <li>• Locking ring from AISI 316 stainless steel.</li> <li>• 15mm clear flat tempered glass cover.</li> </ul>				
CODE			DESCRIPTION	T	COLOUR	PRICE LIST
						Integrated Control Gear
842265	○ 80 61 033	2x15°	1x max.75W PAR30 / E27	152°C	Inox	
842275	□ 80 62 033					
842285	○ 80 61 040	2x3°	1x20W HIT-TC-CE / G8.5	55°C	Inox	
842295	□ 80 62 040					
842303	○ 80 61 041	2x6°	1x20W HIT-TC-CE / G8.5	55°C	Inox	
842313	□ 80 62 041					
804203	<b>Outercasing</b> 89 45 030					

		OSRAM: HALOSPOT 111 PHILIPS: ALULINE 111 OSRAM: DULUX D PHILIPS: PL-C OSRAM: DULUX T / E PHILIPS: PL-T / 4P OSRAM: HCI-T PHILIPS: CDM-T OSRAM: HQI-TS, HCI-TS PHILIPS: MHN-TD, CDM-TD OSRAM: NAV-TS PHILIPS: -	<b>2100 MEDIO Inox</b> <b>DRIVE OVER</b>			
		<ul style="list-style-type: none"> <li>• Body from aluminium alloy.</li> <li>• Locking ring from AISI 316 stainless steel.</li> <li>• 15mm clear flat tempered glass cover.</li> </ul>				
CODE			DESCRIPTION	T	COLOUR	PRICE LIST
						Integrated Control Gear
842345	○ 80 61 096	2x25°	1x18W TC-D / G24d-2	42°C	Inox	
842355	□ 80 62 096					
842365	○ 80 61 162	2x51,8°	1x26 or 32W TC-TEL / GX24q-3	50°C	Inox	
842375	□ 80 62 162					
842385	○ 80 61 080	2x3°	1x35W HIT-CE / G12	60°C	Inox	
842395	□ 80 62 080					
842405	○ 80 61 081	2x6°	1x35W HIT-CE / G12	60°C	Inox	
842415	□ 80 62 081					
842555	○ 80 61 083	2x34°	1x35W HIT-CE / G12	60°C	Inox	
842565	□ 80 62 083					
842575	○ 80 61 085	asym. 16°	1x35W HIT-CE / G12	60°C	Inox	
842585	□ 80 62 085					
842425	○ 80 61 110	2x3°	1x70W HIT-CE / G12	133°C	Inox	
842435	□ 80 62 110					
842445	○ 80 61 111	2x6°	1x70W HIT-CE / G12	108°C	Inox	
842455	□ 80 62 111					
842925	○ 80 61 113	2x34°	1x70W HIT-CE / G12	98°C	Inox	
842935	□ 80 62 113					
842945	○ 80 61 115	asym. 16°	1x70W HIT-CE / G12	89°C	Inox	
842955	□ 80 62 115					
842465	○ 80 61 134	2x16,4°	1x70W HIT-DE or HST-DE / RX7s	105°C	Inox	
842475	□ 80 62 134					
804204	<b>Outercasing</b> 89 45 031					

**T** Glass surface temperature.

Roll over weight 4.000kg.



For the proper installation of the fitting an effective drainage as well as a 20-30 cm deep layer of gravel must be intended for dewatering.



Fittings come with H07RNF cables, 1m length.