













			<b>2100 MEDIO / 2100 MEDIO Inox - ACCESSORIES</b> HONEYCOMB GRID
			<b>PRICE LIST</b>
<b>CODE</b>	<b>DESCRIPTION</b>	<b>COLOUR</b>	
804202	HONEYCOMB GRID 89 26 000		

		Anti-vandalism protection grid "GPA".	<b>2100 MEDIO - ACCESSORIES</b> ANTI-VANDALISM PROTECTION GRID
			<b>PRICE LIST</b>
<b>CODE</b>	<b>DESCRIPTION</b>	<b>COLOUR</b>	
804205	ANTI-VANDALISM GRID 89 42 000		


		Round stainless steel grid	<b>2100 MEDIO - ACCESSORIES</b> ROUND GRID
			<b>PRICE LIST</b>
<b>CODE</b>	<b>DESCRIPTION</b>	<b>COLOUR</b>	
804206	ROUND GRID 89 07 000		

		Square stainless steel grid.	<b>2100 MEDIO - ACCESSORIES</b> SQUARE GRID
			<b>PRICE LIST</b>
<b>CODE</b>	<b>DESCRIPTION</b>	<b>COLOUR</b>	
804207	SQUARE GRID 89 09 000		

		<p> OSRAM: HALOSPOT 111 PHILIPS: ALULINE 111</p> <p> OSRAM: HCI-T PHILIPS: CDM-T</p> <p> OSRAM: HQI-TS, HCI-TS PHILIPS: MHN-TD, CDM-TD</p>	<p> PAR 30</p> <p> OSRAM: NAV-TS PHILIPS: -</p>	<p><b>2100 MEDIO</b> <b>Double glass</b> <b>COOL TOUCH</b></p> <p> </p> <p> </p>
		<ul style="list-style-type: none"> <li>• Body from aluminium alloy.</li> <li>• Locking ring (flange) from aluminium alloy.</li> <li>• 12mm clear flat tempered glass cover.</li> </ul>		
			<b>PRICE LIST</b>	
<b>CODE</b>	<b>DESCRIPTION</b>	<b>T</b>	<b>COLOUR</b>	<b>Integrated Control Gear</b>
842505	80 38 080 2x3° 1x35W HIT-CE / G12	57°C	Black	
842515	80 38 081 2x6° 1x35W HIT-CE / G12	56°C	Black	
842525	80 38 110 2x3° 1x70W HIT-CE / G12	78°C	Black	
842535	80 38 111 2x6° 1x70W HIT-CE / G12	75°C	Black	
842545	80 38 134 2x16,4° 1x70W HIT-DE or HST-DE / RX7s	77°C	Black	
<b>Outercasing (Included)</b>				

**T** Glass surface temperature.

Resistance to static load: max. 500kg



For the proper installation of the fitting an effective drainage as well as a 20-30 cm deep layer of gravel must be intended for dewatering.

Fittings come with H07RNF cables, 1m length.